

Tallowwood

Introduction


Tallowwood flooring has long held a majestic presence in Australia, with its golden honey toning, its exceptional durability and its interesting grain features. Sought by Designers and Architects Tallowwood offers an elegant neutral toned palette, with no compromise on density or durability.

A large tree that grows in the dryer climates of Northern New South Wales and Southern Queensland, Tallowwood is one of the original timber species used for hardwood flooring in Australia.

Species in Detail

Common Names	Tallowwood
Look & Features	Moderately coarse but even texture with an interlocked grain.
Botanical Name	Eucalyptus Microcorys.
Colour	Golden honey brown with a tinge of olive.
Dry Density	990kg/m³
Natural Durability	Class 1d (above ground)

Species Hardness Ratings. Species hardness is measured in Janka numbers - the higher the harder the species.





Product	Widths	Thickness	Install Method	Plywood	Particleboard	Battens	Bearers & Joist
Ultra 10	86mm	10mm	Full Trowel Glue & Secret Nail	V	~		
Overlay	83mm	12mm, 14mm	Full Trowel Glue & Secret Nail	V	V		
FOURTEEN	130mm, 180mm	14mm	Full Trowel Glue & Secret Nail	V	V		
Traditional Flooring	80mm, 130mm	19mm	Secret Nail or Top Nail*	~	~	~	V
Wideboard Flooring	180mm, 210mm	21mm, 23mm	Top Nail	V	~	~	V

*Boards wider than 80mm in traditional flooring should be top nailed as per AS1684.

Select Grade: The Features that are present in Select grade flooring are relatively small and few in number, and although they are visible the features do not dominate the appearance of the floor.

Standard Grade (Medium Feature): Flooring in this grade will be moderately featured. Gum veins, gum pockets, insect trails, burls and borer holes, are some of the characteristic's that will be more prevalent in Standard Grade.

Feature Grade (High Feature): Feature grade flooring is heavily peppered with natural features particularly

Rustic Grade: A full featured floor to provide an old world charm. It may contain features that are more prominent than Feature Grade but with the structural integrity of a Feature Grade Floor.

Environmental Credentials

Complete Floors Australia are committed to our forests, our community and our future.

Underpinning our commitment is an ambitious hardwood reforestation project in our local surrounding area where we have purchase over 5000 hectares of land and have commenced a planting program that will see more than 25000 new plantation eucalypt saplings established each year.

Complete Floors Australia source a proportion of timber from private native forests with the balance procured from NSW State Forestry which is certified under the Australian Forestry Standards Chain of Custody. (AS4707 - 2021).

Complete Floors Australia insist that all timber produced from these forests is done so under the principles of Ecologically Sustainable Forest Management, a system developed to sustain the full range of commercial and conservation values of the natural forest diversity within ecological limits, for current and future generations.











QLD 07 3442 6391 VIC & TAS 03 8794 3390 NSW & ACT 02 4648 3070

SA & NT 08 8794 3390 **WA** 0448 132 955

Email: sales@completefloorsaus.com.au Web: www.completefloorsaustralia.com.au

